



GILTGRIP 1000 SB Primer

SOLVENT BASED FLOORING PRIMER ¹

Issue 2 (08.11.04)

- Easy application
- Interior or exterior applications
- Improves adhesive bond strength
- Primer for many solvent based adhesives
- Flexible

DESCRIPTION

1000 SB Bonding Primer is a thin, brushable or sprayable liquid which can be easily and quickly applied to reinforce the bonding surface on absorbent materials, such as wood, concrete, cement board etc. before applying Bostik Adhesives.

PURPOSE FOR USE

Giltgrip1000 SB Flooring Primer is formulated to be applied to concrete, cement sheet or wooden subfloors and used primarily in conjunction with polychloroprene based adhesives such as BSR 555 and 1222. Surfaces must be clean and dry. If the substrate is very porous, two coats of 1000 Primer should be applied to concrete,

LIMITATIONS

Because of the wide range of surfaces and floorings, a test of any new combination should be conducted before using.

PREPARATION

Ensure the surface is even, clean, dry and free from oil, dust or flaking paint. Ensure concrete subfloors are free from hydrostatic pressure, and test moisture content prior to priming or laying floor covering.

Refer to AS/NZS 2455.1.1995 Part 1 and AS 1884-1985 for installation practice and maintenance.

APPLICATION & COVERAGE RATE

Do not apply adhesive if temperature is below 10°C. Shake or stir before use.

Spread 1000 SB Primer evenly with a brush, roller or spray gun.

Coverage rate: typically 5 square metres per litre although this can vary widely depending on porosity of the substrate.

Drying time is 30 to 40 minutes at 25°C

TYPICAL TECHNICAL DATA

Base: Polychloroprene
Colour: amber
Viscosity: Thin liquid
Solids: 12 %

PACKAGING

Available in 4 tins and other sizes on request.

CLEAN UP

Tools should be washed with Bostik No.2 solvent whilst Primer 1000 is still wet.

SAFETY PRECAUTIONS

Giltgrip 1000 SB Primer is highly flammable. Suitable precautions must be taken. A Material Safety Data Sheet is available on request.

STORAGE & SHELF LIFE

Store out of direct sunlight, keep in original containers tightly closed when not in use. Store in an approved area for Class 3 (flammable) liquids.

Shelf life: minimum 12 months from date of manufacture if stored under cover below 25°C.

Bostik Technical Services are available to pre-test any samples of substrate where the specifier / applicator may believe doubts on application suitability exists.

The tests will aid in determining the proper surface preparation method. Following this procedure will remove many of the unknown variables that affect field success. Please contact your Gilt Edge Industries for further details.

WARRANTY

Your purchase of this product is subject to Bostik's standard terms and conditions of sale. The representation and recommendations regarding the products are based on tests which we believe to be reliable. However, no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes.

Under no circumstances will Bostik be liable to anyone except for replacement of the products or refund of the purchase price.

All other warranties whether express or implied, including without limitation, any warranty of merchantability of fitness of purpose are expressly disclaimed unless prohibited by law or given in writing by Bostik for a specific project.

ALL SALES ARE EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS OF SALE OF BOSTIK NZ Limited.

Distributed by Gilt Edge Industries Limited

Auckland	Phone 09 443 7067	Christchurch	Phone 03 379 7067
Wellington	Phone 04 569 7067	Dunedin	Phone 03 455 7067