
BOSTIK NEW ZEALAND LTD
19 EASTERN HUTT RD
LOWER HUTT
PHONE : (04) 567-5119

National Poisons and Hazardous Chemicals Information Centre:
0800POISON
0800 764 766

PRODUCT : Giltgrip Pressure Sensitive Adhesive

SECTION I IDENTIFICATION Giltgrip Pressure Sensitive Adhesive

UN Number : Not Applicable
Hazchem code : Not Applicable
NZ Dangerous Good class : Not Applicable
Packaging Group : Not Applicable

SECTION II HAZARDOUS INGREDIENTS Giltgrip Pressure Sensitive Adhesive

None

SECTION III PHYSICAL DATA Giltgrip Pressure Sensitive Adhesive

VAPOUR PRESSURE IN MM HG 18
BOILING POINT IN DEGS C 100
VAPOR DENSITY (AIR=1) 1.26
SOLUBILITY IN WATER 100.0 %
EVAPORATION RATE 1.0 (Butyl Acetate=1)
SPECIFIC GRAVITY 1.05
PERCENT VOLATILE BY WEIGHT Approx 48

APPEARANCE AND ODOUR Thick white paste with slight sweet odour.

SECTION VI REACTIVITY DATA Giltgrip Pressure Sensitive Adhesive

STABILITY Stable

MATERIALS TO AVOID Strong Oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS

Unknown due to the complex nature of this material. Fumes from complete or incomplete combustion of this material may include carbon dioxide, carbon monoxide, water vapour, oxides of nitrogen or a wide variety of innocuous or toxic fumes.

HAZARDOUS POLYMERIZATION Will not occur.

SECTION VII SPILL OR LEAK PROCEDURES Giltgrip Pressure Sensitive Adhesive

STEPS TO BE TAKEN WHEN MATERIAL IS SPILLED OR RELEASED

Soak up liquid with an absorbent material such as sand, earth, sweeping compound or some other absorbent material. Package absorbent material or solid product in steel drums which are in good condition. Thoroughly clean area where spill occurred.

WASTE DISPOSAL METHOD

Dispose of in accordance with local rules. Be aware that local requirements may differ widely depending on location and may in many cases be different from national rules. When intending to dispose of this material, the user is advised that this product may be classified as a Hazardous Waste under Regulations in effect at the time this MSDS was created.

SECTION VIII SPECIAL PROTECTION INFORMATION Giltgrip Pressure Sensitive Adhesive

VENTILATION

Not necessary but may be desirable to reduce odours.

PROTECTIVE GLOVES

Not normally required

EYE PROTECTION

Not normally required but is desirable as with handling any industrial product.

OTHER PROTECTION

Safety shower and eye bath.

SECTION IX SPECIAL PRECAUTIONS Giltgrip Pressure Sensitive Adhesive

PRECAUTIONS FOR HANDLING AND STORING

Store in a cool location (15-25 degrees C) away from sunlight and any source of heat. Keep container tightly closed when not being used.

OTHER PRECAUTIONS

Use with adequate ventilation, avoid prolonged or repeated breathing of vapors. Avoid skin contact.

PREPARED BY: Bostik New Zealand Ltd 11 Feb 2004

(Version 1)

IMPORTANT NOTICE:

The above recommendations are intended for the assistance of users and are of a general nature. They are based on our experience and judgement but because the conditions under which, and the materials with which our products are used, are beyond our control our recommendations must not be regarded as amounting to legal warranty or as involving any liability on us.