

Product

Polymer 266

Page 1 of 4

MATERIAL SAFETY DATA SHEET

Date of Issue

10 February 2006

EMERGENCY TELEPHONE NO:

(09) 267 2772 (Work Hours)

IDENTIFICATION

PRODUCT NAME:	Polymer 266
OTHER NAMES	Fibabond Plus
MANUFACTURERS PRODUCT CODE:	PE.A266
U.N. NO.:	None Allocated
DANGEROUS GOODS CLASS:	Not Dangerous
HAZCHEM CODE:	None Allocated
POISON SCHEDULE:	None Allocated

USE

MAJOR RECOMMENDED USES:	Used to adhere vinyl sheet or tiles to concrete and wooden floors
MAJOR RECOMMENDED METHOD OF APPLICATION:	Hand held notched trowel

PHYSICAL DESCRIPTION / PROPERTIES

APPEARANCE: White Semi-Liquid Paste	FLASH POINT: Non-Flammable
-------------------------------------	----------------------------

BOILING POINT (760 mmHg): 100oC

FLAMMABILITY LIMITS:

Upper: Lower: Non-Flammable

VAPOUR PRESSURE (mm @ 25oC):
17.5mmHg

SOLUBILITY IN WATER: Miscible

SPECIFIC GRAVITY: 1.5 kg/1 Approx.

% NON VOLATILES BY WEIGHT: 78 +- 1% W/W

Product

Polymer 266

Page 2 of 4

RLA Polymers (Pty) Ltd

MATERIAL SAFETY DATA SHEET

HAZARDOUS INGREDIENTS

Chemical Entity	Cas. No.	Proportion
MIXED ACRYLATE MONOMERS	-	TRACE
ALIPHATIC SOLVENT	-	< 3% W/W

HEALTH HAZARD INFORMATION

Health Effects: Acute

Swallowed:

If large amounts are ingested this may cause nausea and/or vomiting

Eye:

Possible irritant to eyes

Skin:

May cause irritation. Prolonged contact may cause dermatitis

Inhaled:

Headaches, nausea, may occur if exposed to vapours for long periods.

Health Effects: Chronic

No delayed effects reported

Product

Polymer 266

Page 3 of 4

RLA POLYMERS (PTY) LTD

MATERIAL SAFETY DATA SHEET

FIRST AID

Swallowed:

If large amounts are swallowed, give copious amounts of water to drink. Advise a doctor immediately.

Eye:

Wash eyes thoroughly with copious quantities of fresh water, lifting eyelids occasionally. If pain persists see a doctor.

Skin:

Remove all contaminated clothing and wash affected area with lots of water

(and soap if available). If irritation persists see a doctor.

Inhaled:

Unlikely to cause irritation, however if symptoms exist

remove affected person to fresh air. If any symptoms persist call a doctor immediately.

Advice to Doctor

Nothing extra advised

PRECAUTIONS FOR USE

Exposure (TLV - TWA):

Mixed acrylate monomer - no threshold limit established;

Ventilation:

Normal Ventilation is sufficient;

FLAMMABILITY

Fire Hazard:

None as product is non-flammable.

Sources of Ignition Advice:

None as product is non-flammable.

PERSONAL PROTECTION

Respiratory Protection:

N/A

Glove Type:

Neoprene type.

Eye Protection:

If spraying or splashing likely to occur - wear safety glasses with side shields.

Clothing:

Work clothing covering legs and arms.

Product

Polymer 266

Page 4 of 4

RLA POLYMERS (PTY) LTD

MATERIAL SAFETY DATA SHEET

SAFE HANDLING INFORMATION

Storage and Transport:

Store on wooden pallet, store between 5oC - 30oC. Product is classed as non-dangerous for transport.

Spills and Disposal:

Scoop up and place in a suitable container for disposal. Don't allow spills into waterways. Dispose as per Local Government laws.

Fire Explosion Hazard:

None as product is non-flammable.

Dangerous Decomposition Products:

None expected.

Fire Fighting Recommendations:

Use Carbon Dioxide, Powder and Foam Extinguishers. Water Fog can be used.

CONTACT POINT

RLA POLYMERS (PTY) LTD
67 Dalgety Drive, Wiri
AUCKLAND

TITLE: Technical Manager
TELEPHONE: (09) 267 2772

NOTE: The information and recommendations contained in this data sheet have been compiled from sources believed to be reliable and represent the best current opinion on the subject. No warranty, guarantee or representation is made by the company as to the absolute correctness or sufficiency of any representation contained in this data sheet and the company assumes no responsibility in connection therewith. Nor can it be assumed that all acceptable safety measures are contained in this data sheet or that other additional measures may not be required under particular or exceptional circumstances or conditions.