

Gilt Grip Direct 25

DIRECT STICK CARPET ADHESIVE

DESCRIPTION

Gilt Grip Direct 25 is a water based trowelable adhesive for Direct Stick bonding of carpet. It displays high initial grab and good early bond strength.

- Low Odour / Water Based
- High Initial Grab
- High Early Bond Strength

PURPOSE FOR USE

Gilt Grip Direct 25 bonds jute, latex, Action Back, woven, foam back and needle punch carpet to concrete and wooden subfloors.

LIMITATIONS

Because of the wide range of surfaces and floorings, a test of any new combination should be conducted before using. Not recommended for: Oily timber, Oil tempered particleboard, External use.

PREPARATION

Ensure the surface is even, clean, dry and free from oil, dust or flaking paint. A very porous or highly absorbent surface (eg. concrete or wood) should be primed first with Anchor-Weld PR1 Primer.

Ensure concrete subfloors are free from hydrostatic pressure, and test moisture content prior to priming or laying floor covering.

APPLICATION & COVERAGE RATE

Refer to refer to AS/NZS2455.1-1995 A Textile Floor Coverings - Installation Practice, Part 1: General for further preparation and laying details.

Do not apply adhesive if temperature is below 10 °C. Spread CA1 evenly with a AV= notch trowel.

Smooth backed carpets:

Trowel: 2.4 mm V-notch (coverage approx. 3 m²/L)

Ideal Open time: 20 minutes

Coarse backed carpets:

Trowel: 3.2 mm V-notch (coverage approx. 2 m²/L)

Ideal Open time: 30 minutes

The adhesive must be allowed to tack up and develop some grab before laying in the floor covering. This can be assessed by lightly pressing your finger onto the surface of the adhesive then pulling away - tack up is observed when the adhesive appears stringy / leggy.

Ensure adhesive transfer occurs into the carpet backing.

Note: Open time is influenced by substrate porosity and atmospheric conditions (ie. Temperature, humidity, air movement).

Roll the installation using a 25 - 35 kg roller in both directions immediately after laying. Then re-roll after 20 minutes.

Avoid heavy traffic for 24 hours after installation.

TYPICAL TECHNICAL DATA

Base:	Latex
Colour:	Off White
Viscosity:	Thick paste
Solids:	50% ± 2%

PACKAGING

Available in 20L pails

SHELF LIFE :

12 months if stored in cool, dry conditions in original, unopened containers.

FLAMMABILITY :

The adhesive is highly flammable, do not open container within 10 metres of fire or flame. Use in well ventilated areas.

Wellington Site (Factory & Admin)
Auckland Site
Christchurch Site

19 Eastern Hutt Road, Wingate, Lower Hutt
148 Pavillion Drive, Airpark II, Auckland Airport
39 Leslie Hills Drive, Riccarton, Christchurch

Ph ++64 4 567 5119 Fax ++64 4 567 5412
Ph ++64 9 257 5847 Fax ++64 9 257 3588
Ph ++64 3 364 9575 Fax ++64 3 364 9576

www.bostik.co.nz

The recommendations given on this document are intended for the assistance of users and are of a general nature. They are based on our experience and judgement but because of the conditions under which, and the materials with which our products are used are beyond our control, our recommendations must not be regarded as amounting to any legal warranty or as involving any liability on us.

HEALTH AND SAFETY

Fuller details on each of the products mentioned are available on the product Safety Data Sheets. To ensure no harm is caused to persons using Bostik products, it is recommended that the appropriate Safety Data Sheets are read by all concerned. Visit www.bostik.co.nz for copies.

FIRST AID

Swallowed Do not induce vomiting, give a glass of water and contact a doctor immediately.

Skin Remove contaminated clothing, wash with warm soapy water. Do not scrub.

Inhaled Remove person to fresh air. Get medical advice if breathing becomes difficult. If inhaled to excess, remove from contaminated area – apply artificial respiration if not breathing.

Eyes Hold open and flood with water for at least 15 minutes. Get medical advice.

For emergency information contact the National Poisons Information Centre, phone 0800 764 766 (0800 POISON) or CHEMICALL, phone 0800 243 622.

DISPOSAL

If spilt, absorb with clay, sand or earth. Collect and seal in properly labelled metal containers. Dispose of according to local authority regulations. Do not dispose of down drains or into local waterways.

VERSION February 2009

Wellington Site (Factory & Admin)	19 Eastern Hutt Road, Wingate, Lower Hutt	Ph ++64 4 567 5119	Fax ++64 4 567 5412
Auckland Site	148 Pavillion Drive, Airpark II, Auckland Airport	Ph ++64 9 257 5847	Fax ++64 9 257 3588
Christchurch Site	39 Leslie Hills Drive, Riccarton, Christchurch	Ph ++64 3 364 9575	Fax ++64 3 364 9576

www.bostik.co.nz

The recommendations given on this document are intended for the assistance of users and are of a general nature. They are based on our experience and judgement but because of the conditions under which, and the materials with which our products are used are beyond our control, our recommendations must not be regarded as amounting to any legal warranty or as involving any liability on us.