



GILTGRIP HIGH TACK ADHESIVE

DESCRIPTION:

Giltgrip High Tack Adhesive is a solvent based trowel applied adhesive for bonding synthetic backed carpet on concrete or timber. Giltgrip High Tack Adhesive has an exceptionally strong initial grab and gap filling to ensure the best possible bond to most interior surfaces. It exhibits good water resistant bonds and water damage even after 5 hours will not affect the bond even if the adhesive becomes flooded.

PROPERTIES:

Type:	Synthetic/rubber/resin
Solvent:	Hydrocarbon mixture
Flash point:	Below 0 deg C
Colour:	brown paste
Viscosity:	Thick paste
Temperature range:	Satisfactory between -20°C and 80°C dependent on bond line stress.
Bonding range:	Up to 10 minutes maximum at 25°C. If this not observed, poor bonding will result due to poor adhesive transfer and wetting on the carpet backing.
Coverage:	Approximately 2 sq. metres of bonded area per litre, dependent upon porosity of surface applied to.
Cleaner:	Bostik No.3 or 2 Solvent
Thinner:	Bostik No 3 Solvent ONLY.
Shelf life:	12 months if stored in cool, dry conditions in original, unopened containers.
Location:	Interior surfaces only.

METHOD OF APPLICATION – Notched trowel :

***** MIX THOROUGHLY BEFORE USE *****

1. Ensure surfaces to be bonded are clean and dry and free from dust, dirt, grease or other contaminants.
2. Apply the adhesive over floor surfaces with trowel.
3. After 10 minutes or sooner, place the carpet on the wet adhesives.
4. Apply even pressure over the carpet with a heavy roller to facilitate adhesive transfer and bonding.
5. After 30 minutes, use a suitable roller over the carpet again especially around the joints and edges to ensure good contact between carpet and adhesive. This is most important.

PACKAGING:

20 Litres containers.

STORAGE :

Wellington Branch, Factory & Office	Ph:(04) 567 5119	Fax:(04) 567 5412
Auckland branch	Ph:(09) 579 9263	Fax:(09) 579 6239
Christchurch Branch	Ph:(03) 366 2583	Fax:(03) 366 2582



The recommendations given on this document are intended for the assistance of users and are of a general nature. They are based on our experience and judgement but because of the conditions under which, and the materials with which our products are used are beyond our control, our recommendations must not be regarded as amounting to any legal warranty or as involving any liability on us.

Store in cool, dry conditions out of direct sunlight below 25°C and away from naked flame or sources of heat.

TRANSPORT :

Proper Shipping Name:	ADHESIVES
Hazard Class:	3
UN Number:	1133
Hazchem Code:	3[Y]E
Packaging Group:	11

VERSION :

Version 1	31 st May 2006
-----------	---------------------------

IMPORTANT NOTICE:

The above recommendations are intended for the assistance of users and are of a general nature. They are based on our experience and judgement but because the conditions under which, and the materials with which our products are used, are beyond our control our recommendations must not be regarded as amounting to legal warranty or as involving any liability on us.