



## Giltgrip 44 Premium Vinyl Adhesive

### PRODUCT DESCRIPTION

Giltgrip 44 is Hi-Grab Vinyl Plank and Sheet Vinyl Adhesive with Low in VOC It is a high performance acrylic based adhesive designed for the installation of commercial and domestic sheet vinyl and PVC plank and tiles. It is **not** recommended for the installation of linoleum.

It has an excellent plasticizer resistance and is formulated to provide quick initial grab and exhibit excellent “re-bond” characteristics.

### SURFACE PREPARATION

To be in accordance with The Australian/NZ Standard 1884-1985 “Floor Coverings – Resilient Sheet and Tiles – Laying and Maintenance Practices”. All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease and hydrostatic pressure. The minimum subfloor temperature before commencing surface preparation and adhesive applications 10 degrees C.

Highly absorbent wooden or concrete subfloor surfaces are to be primed with suitable Acrylic Primer prior to the application of adhesive.

All concrete substrate floors should be tested for moisture content, according to the above Australian/NZ Standard prior to undertaking surface priming or installation of floorcoverings.

### APPLICATION

Spread adhesive with a 1.6mm x 1.6mm x 1.6mm ‘V’ Notched trowel. Some domestic sheet vinyl may require a fine 1.6mm x 0.8 x .08 trowel to prevent adhesive ‘show trough’. Adhesive must be allowed to tack-up before floorcoverings is lowered. Tack-up time will depend upon atmospheric conditions and can be anywhere between 10-20 minutes. It is good practice to place a small piece of floorcoverings into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent.

If no tack or holding power has developed, wait five minutes before rechecking every few minutes thereafter.

Complete installation according to vinyl manufacturer’s instructions, ensuring the installation is rolled in both directions with the recommended roll weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam-sealed using suitable vinyl seam sealer.

### CLEAN UP

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using a solvent cleaner applied to a damp cloth then rubbed gently over the dried adhesive.

### TYPICAL PROPERTIES

Appearance	Cream / White
Base	Acrylic
Solids	Approx 70%
Viscosity	60,000-70,000 Brookfield RVT
Shelf Life	Up to 1 year in sealed container at 20°C
Freezability	Do not freeze
Container Size	15 Litre plastic pail
Tack-up	10-15 minutes at 20°C
Trowel Size	1.6mm x 1.6mm x 1.6mm ‘V’ notched

**COVERAGE** Up to 5m<sup>2</sup> per litre

Every Flooring Installation Deserves the “GILT EDGE” Finish

<b>Auckland</b> 37 Fairfax Ave Penrose Ph 09 579 7067 Fax 09 579 7064	<b>Auckland</b> 3/7 Colway Place Glenfield Ph 09 443 7067 Fax 09 444 0510	<b>Whangarei</b> 2 Mill Road Ph (0274) 364 642	<b>Hamilton</b> 40 Te Kowhai Dr Te Rapa Ph 027 223 4147	<b>Tauranga</b> 45 Totara St Mt Maunganui Ph 027 223 4147	<b>Palmerston North</b> 1021 Tremaine Ave Ph 0274 364 646	<b>Wellington</b> 50 Fitzherbert St Petone Ph 04 569 7067 Fax 04 569 7066	<b>Christchurch</b> 47 Carlyle St Sydenham Ph 03 379 7067 Fax 0800 103 649	<b>Timaru</b> 17 Butler St Ph (0274) 387 266	<b>Dunedin</b> 15 Turakina Rd South Dunedin Ph 03 455 7067 Fax 03 455 7069	<b>Nelson</b> 8 Washington Rd 0274 387 266
---	---	--	--	--	---	---	--	--	--	--