

12 ACRYLIC SHEET VINYL ADHESIVE

PRODUCT DESCRIPTION

Roberts 12 Acrylic Sheet Vinyl Adhesive is an acrylic based adhesive with excellent plasticiser resistance specifically formulated for the installation of commercial and domestic vinyl floorcoverings. It has high initial grab and is ideal for bonding both supported and unsupported PVC vinyls.

It is not recommended for linoleum.

SURFACE PREPARATION:

To be in accordance with the Australian Standard 1884-1985 "Floor Coverings - Resilient Sheet and Tiles - Laying and Maintenance Practices".

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease & hydrostatic pressure.

The minimum subfloor temperature before commencing surface preparation and adhesive application is 10°C.

It is recommended that all wooden and concrete subfloors be primed with **Roberts 370 Floor & Wall Primer** prior to the application of adhesive. For other subfloor surfaces, please contact your distributor.

All concrete substrate floors should be tested for moisture content, according to the above Australian Standard, prior to undertaking surface priming or installation of floorcoverings.

APPLICATION:

Spread adhesive with the recommended notched trowel. Adhesive must be allowed to tack-up before floorcovering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floorcovering into the adhesive. When the floorcovering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes rechecking every few minutes thereafter.

Complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller weight, prior to the adhesive setting. Do not allow heavy traffic for 24 hours.

All seams for domestic vinyl should be seam sealed with **Roberts 5601 Vinyl Seam Sealer**.

CLEAN UP:

Clean tools immediately after use with warm soapy water. Dried adhesive may be cleaned off using **Roberts 550 Adhesive Softener** applied to a damp cloth then rubbed gently over the dried adhesive.

For removing old adhesives from the floor prior to the laying of new vinyl it is recommended **Roberts 550 Adhesive Softener** be used.

Roberts 550 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

TECHNICAL DATA

Appearance:	Creamy
Base:	Acrylic
Solids:	Approx. 68%
Viscosity:	Trowellable
Shelf Life:	Up to 1 year in sealed container at 20°C
Freezability:	Do not freeze
Packaging:	20 litres
Tack-Up:	10-15 minutes at 20°C
Trowel Size	Smooth backed vinyl 1.6mm x 1.6mm x 1.6mm "V" notched
Coverage	up to 5m ² /litre

Material Safety Data Sheet available upon request

Disclaimer: Information given on this data sheet, is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to RLA Polymers Pty Ltd as below.
