

Polymer 300 Contract Carpet Adhesive

GENERAL DESCRIPTION

Polymer 300 Contract Carpet Adhesive is an acrylic blend, with special features such as vigorous, extended tack time.

FOR

Action bac, hessian back, and most woven carpets, either in a double stick situation, or directly to the subfloor.

TO

Latex foam carpet underlay, or for adhering latex foam underlay and the various carpet types (as above) directly to sound subfloor. Can be used on timber, concrete, or other underlayments.

To be used in accordance with Australian Standard 2455.1.1995 "Textile Floor Coverings Installation Practice".

PREPARATION

Concrete

Concrete must be free of dirt, dust, grease, oil, paint, etc. Check to ascertain if curing, water-proofing agents have been used which could impair drying or adhesion.

Adhesive must not be used where water pressure or excessive water by capillary action is present, i.e. check whether a damp proof membrane is included in the sub-floor construction and with new concrete, whether adequate drying time has elapsed. In all cases, moisture testing of slabs is highly recommended.

Timber

Timber floors must be dry and free of dirt, dust, grease, oil, paint etc. Care must be taken that floor sanders have not used solvents excessively in sweeping off. Floors must be well ventilated underneath. Priming with Polymer 6000 is recommended.

APPLICATION

Apply adhesive with the appropriate V-notched spreader. The depth of the notch should be 2.0 - 2.5mm for hessian backed carpets, and 2.5 - 3.0mm for action-bac carpets, woven, or other highly textured back carpets. Roll within 1 hour of laying.

COVERAGE

Approximately 3-5 square metres per litre depending on size of notched trowel used, and the absorbency of the subfloor.

TECHNICAL DATA

Type: Single stick, water borne
Composition: Water based latex/acrylic blend
Colour: White
Shelf Life: 12 months minimum
Flash Point: Non-flammable
Open Time: Approx. 15-20 minutes

CLEAN UP

Any **Polymer 300 Contract Carpet Adhesive**, on the surface of the carpet should be removed immediately with a well dampened cloth. Do not allow to dry. Trowels and other tools, or dried adhesive will only be cleaned with solvents.

SHELF LIFE

12 months minimum in unopened containers, stored under appropriate conditions.

STORAGE

Recommend to be stored at temperatures between 5 & 30°C away from direct heat. Do not allow to freeze.

Disclaimer: Information given on this data sheet is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to Gilt Edge Industries Ltd, Akld Ph: 09 443 7067, Wgtn Ph: 04 569 7067, Chch Ph: 03 389 7067, Dudn Ph: 03 455 7067
