



5216 CARPET SEAM ADHESIVE

PRODUCT DESCRIPTION

Roberts 5216 Carpet Seam Adhesive is a solvent based (flammable) contact adhesive used for bonding carpet seams together when a direct-stick or Double-Bond installation method is used.

Roberts 5216 Carpet Seam Adhesive is a rapid drying, heat resistant adhesive which develops a high bond strength.

APPLICATION:

Seams must be clean, dry, and free from adhesive. Starting at one end of the seam, apply a 3.0mm bead along the length of the seam using a Seam Adhesive Applicator.

HIGHLY FLAMMABLE

Avoid contact with skin and eyes and avoid breathing vapour.

FIRST AID

If poisoning occurs, contact a Doctors or Poisons Information Centre.

If swallowed, do NOT induce vomiting. Give a glass of water.

SAFETY DIRECTIONS

Storage of this product is controlled by Local, State and Commonwealth Government Regulations.

Store in a well ventilated area away from oxidising agents.

In use, please ensure that Occupational Health and Safety requirements are observed. Work areas should be well ventilated and free of ignition sources. Prolonged skin contact or inhalation of vapours is advised against.

CLEAN UP:

To clean up equipment and adhesive spills, use Roberts 900 Cleaner/Thinner (Flammable).

Roberts 900 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

TECHNICAL DATA

Appearance: Light Yellow Fluid

Base: Neoprene Synthetic Rubber

Solids: Approx. 21%

Viscosity: Thin Syrup

Flash Point: Less than 0°C

Shelf Life: Up to 1 year in sealed container at 20°C

Packaging: 1 litre

Contains: 520ml/litre Liquid Hydrocarbons
170ml/litre Ketones

Material Safety Data Sheet available upon request

Disclaimer: Information given on this data sheet, is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to RLA Polymers Pty Ltd as below.