



# 5601 VINYL SEAM ADHESIVE

## PRODUCT DESCRIPTION

**Roberts 5601 Vinyl Seam Adhesive** is a specially formulated flammable solution for chemically welding vinyl sheet flooring seams.

Not recommended for vinyl sheet flooring with a urethane wear surface.

## SURFACE PREPARATION

Seams must be dry and free of adhesive. Wipe the seam area with a clean cloth dampened with water. Allow area to dry before applying **Roberts 5601 Vinyl Seam Sealer**.

## APPLICATION:

To be used with an applicator bottle.

Do not shake **Roberts 5601 Vinyl Seam Sealer** within half an hour before using to avoid air bubbles.

Transfer **Roberts 5601 Vinyl Seam Sealer** to applicator bottle and reseal container tightly. Starting at one end of the seam, insert the applicator tip into the seam and apply a continuous bead along the entire length of the seam. Avoid excessive downward pressure and maintain continuous pressure to the applicator bottle during the sealing process.

## TECHNICAL DATA

**Appearance:** Clear Liquid

**Base:** Synthetic Resins

**Solids:** Approx. 21%

**Viscosity:** Thin syrup

**Flash Point:** Less than 0°C

**Shelf Life:** Up to 6 months in sealed container at 20°C

**Packaging:** 500ml

**Contains:** 850ml/litre Ketones

## CAUTION - HIGHLY FLAMMABLE

Contains Flammable Solvents - Use in a ventilated area away from flame or sparks. Store in a tightly sealed container in a cool, dry place.

Do not smoke when applying the adhesive and always seal the container when not in use, to avoid accidental fire.

## HIGHLY FLAMMABLE

Avoid contact with skin and eyes and avoid breathing vapour.

## FIRST AID

If poisoning occurs, contact a Doctors or Poisons Information Centre.

If swallowed, DO NOT induce vomiting. Give a glass of water.

## SAFETY DIRECTIONS

### Storage

Storage and use of this product is controlled by Local, State and Commonwealth Government Regulations.

Store in a well ventilated area away from oxidising agents.

In use, please ensure that Occupational Health and Safety requirements are observed. Work areas should be well ventilated and free of ignition sources.

Prolonged skin contact or inhalation of vapours is advised against.

## CLEAN UP:

Clean tools immediately after use with Roberts 550 Latex/Acrylic Adhesive Remover. Dried adhesive may be softened and lifted with Roberts 550 Latex/Acrylic Adhesive Remover. Roberts 550 is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

Disclaimer: Information given on this data sheet, is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to RLA Polymers Pty Ltd as below.

*Material Safety Data Sheet available upon request*