



Roberts 59 CONTRACT CARPET ADHESIVE

PRODUCT DESCRIPTION

Roberts 59 Carpet Adhesive is water based and specifically formulated to provide a tacky film of adhesive that is strong enough to eliminate any movement in the carpet after installation is completed. It is suitable for both Double-Bond and direct stick installations. Roberts 59 Carpet Adhesive is designed to be used for bonding both the slab underlay to the subfloor and the carpet to the slab underlay.

It is suitable for adhering jute, latex, ActionBac backed carpets and woven carpets along with Textron™ paper, woven polypropylene, cerex, and jute sided latex foam laminated slab underlays.

SURFACE PREPARATION

To be in accordance with the Australian Standard 2455.2:1995 "Textile floor covering-installation practice".

All surfaces to be bonded shall be dry, smooth, sound and clean. Subfloors must also be free of wax, grease & hydrostatic pressure.

The minimum subfloor temperature before commencing surface preparation and adhesives application is 10°C.

It is recommended that all wooden or concrete subfloor surfaces be primed with Roberts 370 Floor & Wall Primer prior to the application of adhesive. For other subfloor surfaces, please contact Roberts Australia or RLA Polymers.

All concrete substrate floors should be tested for moisture content, according to the above Australian Standard, prior to undertaking surface priming or installation of floorcovering.

APPLICATION:

Roberts 59 Carpet Adhesive is to be applied using a long nap roller, or the following types of notched trowel.

2.4mm x 2.4mm x 2.4mm 'V' notched (Roberts 10-353 Switch blade) for laminated foam underlays & smooth backed carpets – Coverage up to 3m²/litre.

3.2mm x 1.6mm x 3.2mm 'V' notched (Roberts 10-354 Switch blade) for textured backed carpets – Coverage up to 2m²/litre.

Strong tack develops rapidly enabling carpet/underlay to be lowered in almost immediately at temperatures in excess of 15°C. In colder conditions, allow adhesive to remain open until tack and grab develop, then lower in carpet/underlay.

Check to ensure that complete transfer of adhesive to the carpet/underlay has occurred. Roll finished installation with a 25-35 kg roller. Complete the installation according to floorcovering manufacturer's instructions. Do not allow heavy traffic for 24 hours. All seams must be sealed using **Roberts 5216 Carpet Seam Adhesive**.

CLEAN UP:

Clean tools immediately after use with warm soapy water. Dried adhesive may be softened and lifted with **Roberts 550 Latex/Acrylic Adhesive Remover**. **Roberts 550** is not recommended for removing adhesive from vinyl, carpet or painted surfaces.

TECHNICAL DATA

Appearance:	Off White
Base:	Latex
Solids:	Approx. 60%
Viscosity:	Trowellable /Rollable
Shelf Life:	Up to 1 year in sealed container at 20°C
Freezability:	Avoid freezing
Packaging:	15 litres

Material Safety Data Sheet available upon request

Contact Gilt Edge: Christchurch 03 3797067
Auckland 09 5797067
help@giltedge.co.nz

Disclaimer: Information given on this data sheet is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to RLA Polymers Pty Ltd as below.