



Roberts 6135 Construction Adhesive

PRODUCT DESCRIPTION

Roberts 6135 Construction Adhesive is a versatile mastic, developed for bonding most common materials used in the construction industry. These include timber, masonry, brick, galvanised iron, steel and polystyrene foam.

The adhesive is a high solids product that forms a very tough, flexible glue base. It is primarily used in sheet flooring and wall panelling, and it may be used in many home repair applications.

SURFACE PREPARATION

Surfaces to be bonded must be clean, dry and free from dust and oil.

TYPICAL PROPERTIES

Appearance	Light Brown
Base	Synthetic Elastomeric Polymer
Flash Point	Less than 0°C
Viscosity	Heavy Mastic
Shelf Life	Minimum 12 months in sealed containers at 20°C

DRYING TIME

Initial bond in 1 to 30 minutes. Handling strength in 30 minutes to 24 hours. All drying times are dependent on porosity of materials and ambient temperature.

CLEAN UP

Clean up excess adhesive and tools with Mineral Turps.

APPLICATION

Roberts 6135 Construction Adhesive should be applied to one surface and the other surface pressed onto the adhesive and held securely in place. For fast setting bonds, separate surfaces for 2 to 5 minutes - reposition and press in place.

Temporary fastening is not normally required when fixing lightweight materials such as polystyrene foam. Manufacturer's nailing instructions must be followed when fixing sheet flooring.

SAFETY DIRECTIONS

Storage

Store in a well ventilated area away from oxidising agents and avoid direct sunlight.

WARNING

Flammable. Always provide adequate ventilation. Keep away from heat, sparks, naked flames etc.

Disposal

Please dispose of empty containers and residue in accordance with your local waste management regulations.

First Aid

If poisoning occurs, contact a Doctor or Poisons Information Centre. Phone 03 474 7000. If swallowed, do NOT induce vomiting. Give a glass of water and see a doctor.

THIS PRODUCT IS LOW IN TOXICITY