

GILT EDGE INDUSTRIES LIMITED
PRODUCT DATA SHEET

Polymer Carpet Direct Latex Adhesive

GENERAL DESCRIPTION

A latex based adhesive with high initial tack, excellent trowellability and superior adhesive properties.

USES

Recommended for hessian backed carpet and carpet tiles, and foam backed carpet in direct stick application. **Polymer Carpet Direct Adhesive is NOT recommended for highly plasticised vinyls or actionbac carpets.**

PREPARATION:

Concrete

Concrete must be dry and free of dirt, dust, grease, oil, paint, etc. Check if curing, water-proofing, or parting agents have been used which could impair drying or adhesion. Adhesive must not be used where hygroscopic pressure or excessive water by capillary action is present, i.e. check whether a damp proof membrane is included in the subfloor construction, and with new concrete, whether adequate drying time has elapsed. Moisture testing of all slabs is strongly recommended. Use proprietary filler or patch to fill holes and cracks to repair floor before applying pressure.

Timber

Timber floors must be dry and free of dirt, dust, grease, oil, paint, etc. Care must be taken that floor sanders have not used solvents excessively in sweeping off. Floors must be well ventilated underneath. Priming with Polymer 6000 is recommended.

APPLICATION:

When laying carpet or carpet tiles:
Use a 2-3mm notched trowel, (Roberts Switchblade #10.353 or similar) is recommended.

Lay floorcovering into wet adhesive within 20 minutes maximum. Roll or smooth out to remove air bubbles (Do not roll if laying foam back carpet).

TECHNICAL DATA

Type: Single stick, water borne

Composition: Rubber latex based emulsion

Colour: White

Shelf Life: 6 months minimum

Flash Point: Non-flammable

Open Time: Approx. 15-20 minutes

Coverage: 3-4sq. metres per litre

Storage: Store between 5°C and 25°C in cool place. Must not freeze.

Clean Up: Water while wet. Toluol when dry.

Pack Size: 20 litres

Solids: 41-44%

Disclaimer: Information given on this data sheet, is to the best available knowledge of the manufacturer, true and correct. However owing to the diverse nature of applications, conditions, and materials used, no guarantee either expressed or implied, can be given. Enquiries should be directed to Gilt Edge Industries Ltd, Akld Ph: 09 443 7067, Wgtn Ph: 04 569 7067, Chch Ph: 03 379 7067, Dudn Ph: 03 455 7067
