

**GILT EDGE INDUSTRIES LIMITED**  
**PRODUCT DATA SHEET**

**POLYMER CCV Carpet & Commercial Vinyl**

**DESCRIPTION:**

Polymer CCV is a modified latex based adhesive with fast initial tack, strong tack build and excellent adhesive properties.

**FOR BONDING:**

Recommended for Commercial Vinyls, Linoleum and Hessian Back carpet and carpet tiles.

**TO:**

Sound, smooth dry subfloors of concrete; conventional sand/cement screeds or underlayment; plywood, hardboard or cement sheet underlays.

Priming is recommended (Polymer 6000) on absorbent surfaces and all timber substrates.

**COVERAGE:**

Approximately 3-6 square metres per litre depending upon the size of the notched trowel used and the absorbency of the subfloor.

**STANDARDS:**

Australian Standard 2455-1989 - "Textile Floor Coverings Laying Practice."

**PREPARATION:**

Thorough subfloor preparation is essential to the successful installation of all floor and wall coverings. The surface must be clean, structurally sound, dry and free from all contaminants which will inhibit good adhesion - this includes previously used adhesives and floor coverings, polishes, paint waterproofing membranes, concrete curing agents and laitence.

Deep indentations and uneven concrete subfloors should be treated with the appropriate cementitious screed in accordance with manufacturers instructions.

**TECHNICAL DATA:**

Appearance:	Off White
Composition:	Rubber Latex Based Emulsion
Type:	Single Stick Water borne
Flammability:	Non- flammable
Open time:	15-20mins approx

**APPLICATION:**

Do not thin but stir if necessary.

When laying Commercial Vinyl:

Apply with a 1.5mm notched trowel (Roberts Switchblade #10-352 or similar) Lay floorcovering into wet adhesive within 15 minutes maximum . Roll or smooth out to remove air bubbles.

When laying carpet or carpet tiles:

Use a 2-3mm notched trowel (Roberts Switchblade #10-353 or similar)

**CLEAN UP:**

Water while wet. Toluol when dry.

**SHELF LIFE:**

12 months in unopened containers stored under appropriate conditions.

**STORAGE:**

Recommended to be at temperatures between 5 and 25degrees Celsius. Keep in well ventilated areas away from sources of heat. Must not freeze.

**SAFETY & HANDLING:**

*A Material Safety Data Sheet* is available on request.

**CONTAINER SIZES:**

20 litre plastic pails.

**GILT EDGE INDUSTRIES LIMITED**

**PHONE: (03) 389 7067**

**FAX: 0800 103 649**

**Manufactured for Gilt Edge Industries Ltd by  
R.L.A. Polymers PTY Ltd**