



GILT EDGE  
INDUSTRIES LIMITED

FLOORING PREPARATION AND INSTALLATION SPECIALISTS

**FLOOR  
PREPARATION  
PRODUCT  
CATALOGUE**

EVERY FLOORING INSTALLATION  
DESERVES THE "GILT EDGE" FINISH

# PRIMERS



**Uzin PE 520 Primer** (UZPE52010) - Water based primer for installations of levelling compounds. For porous substrates. Diluted 4:1 with water for “wet on wet” installations. Install levelling compound while primer is still wet. Can also be used a dry primer without reduction in bond strength. Used as an additive for enhanced flexibility and adhesion in levelling compounds. Ideal primer for adhesive applications. Primer system for aerated concrete substrates. Applied by brush, roller or spray.

**Coverage**  
**Wet Primer** per 10kg  
 30gms/m<sup>2</sup> when diluted 4:1  
**Dry Primer** per 10kg  
 40gms/m<sup>2</sup> when diluted 3:1



**Uzin PE 280 Primer** (UZPE2805) Film smoothing primer for smooth non porous surfaces. Rapid cure. For applications over sound and well bonded existing adhesive residues and screeds. For priming substrates treated with Uzin epoxy based moisture barriers and primers. Primer for timber prepared timber substrates plus T&G. 45 minute cure time.

**Coverage**  
 50 m<sup>2</sup> per 5kg pail



**Uzin PE 460 Primer** (UZPE460) - 2 part epoxy primer for damp or weak substrates. Heavy duty primer for domestic, commercial and industrial use. Maybe blended with aggregates to produce a durable mortar system. Primer for substrates with below 90% moisture content and reducing. Primer for KR430 and KR421 in exterior situations.

**Coverage**  
 30 m<sup>2</sup> per 10kg Kit  
 (as a primer)



**Uzin PE 630 Primer** (UZPE63016) - 2 part (powder & emulsion) trowel applied primer for priming ceramic tiles or T&G timber substrates prior to the installation of floor levelling compounds. Rapid drying primer cures to a profiled, semi flexible compound that reduces joint and grout line appearance in finished levelling. Interior use only.

**Coverage**  
 2-4 m<sup>2</sup> per kg  
 (depending on substrate profile)



**Roberts Universal Primer 5L** (RFPUP5) - This universal primer is a rapid drying solvent free low VOC water based acrylic primer. For use over porous and non porous substrates such as existing tiles, old paint (with the exception of oil based paints) vinyl adhesive, vinyl tiles, carpet adhesive residue, metal surfaces, sealed or burnished concrete floors. Is compatible with cement based ceramic tile adhesive. Can be applied internally or externally over clean dry surfaces.

**Coverage**  
 Approx 5 m<sup>2</sup> to 10m<sup>2</sup> per Litre

# SELF LEVELLING COMPOUNDS



**Uzin NC 145** (UZNC14525) - Self Levelling Compound for thickness up to 4.00mm. For standard substrate preparation under carpet and ceramic tiles in domestic and light commercial situations. Can be laid over after 24 hours. Interior use only. 20MPA

## Coverage

17 m<sup>2</sup> per 25kg bag @ 1.00mm thick  
6 m<sup>2</sup> per 25kg bag @ 3.00mm thick



**Uzin NC 160** (UZNC16020) - Self Levelling water mixed compound. 1.5mm-20mm thickness (5L water). Interior use only. For preparation prior to installation of all floor coverings. **Not for under solid timbers.** 30MPA

## Coverage

4.75 m<sup>2</sup> per 20kg bag @ 3.00mm thick  
1.40 m<sup>2</sup> per 20kg bag @ 10.00mm thick  
(Product can be extended with Uzin sand 2:1)



**Uzin NC 170 Level Star** (UZNC17020) - Self Levelling water mixed compound. High strength. High performance and high flow characteristics. Thickness unlimited (5.25L water). Interior use only **For preparation prior to installation of all floor coverings including solid timber flooring.** 35-40 MPA

## Coverage

4.75 m<sup>2</sup> per 20kg bag @ 3.00mm thick  
1.40 m<sup>2</sup> per 20kg bag @ 10.00mm thick  
(Product can be extended with Uzin sand 2:1)



**Uzin NC 395** (UZNC39525)—Free flowing Interior/Exterior water mixed levelling compound. (4-4.5L water). 3.0mm-40.00mm thickness. Rapid setting. Can be used as substrate preparation for ceramic tiles and stone flooring systems. 25MPA

## Coverage

4-5 m<sup>2</sup> per 25kg bag @ 3.00mm thick  
1-2 m<sup>2</sup> per 25kg bag @ 10.00mm thick



**Gilt Grip LC** (RGGLC)—is a 2 part floor levelling compound consisting of synthetic latex liquid and cementious powder. It is recommended for levelling and repairing concrete floors prior to the installation of resilient flooring products such as vinyl, carpet, cork and ceramic tiles.

## Coverage

4-5 m<sup>2</sup> per kit @ 3.0mm thick

# SKIM COAT / PATCH REPAIR



**Uzin NC 888** (UZNC888) - Very fine and rapid setting flushing compound that finishes to a fine finish edge. Excellent bonding properties to a very wide range of substrates with or without primer. Ideal for repair of small substrate imperfections. For thickness up to 4.0mm. Most installations can be laid on after 30 minutes. Interior use only. Large water ratio variation. Progress sand as soon as dry.

## Coverage

4.1 m2 per 4.5kg bag @ 1.00mm thick  
1.0 m2 per 4.5kg bag @4.00mm thick



**Roberts 35 Fine Patch** (RFPFP3510) - Roberts Fine Patch 35 is a fast drying cementitious underlayment designed for smoothing ridges, patching cracks or holes and feather-edge transitions. Applied as a feather edge, expect to gain anything up to 30sqm, depending on texture of substrate.

## Coverage

8 m2 per 10kg pail @ 1.00mm thick



**Uzin NC 182** (UZNC18220) - Trowel applied strength, rapid cure floor levelling compound. Water mixed (5-6L water). Feather edge—100mm low slump. Very fine surface finish. Interior use only. Recommended that all substrates should be primed. Can be covered after 1 hour. 30 MPA

## Coverage

4.75 m2 per 20kg bag @ 3.00mm thick  
1.40 m2 per 20kg bag @ 10.00mm thick  
(Product can be extended with Silicate sand 2:1)



**Uzin NC366** (UZNC36625) - Trowel applied low slump levelling compound for interior or exterior use. Rapid setting compound suitable for thickness 3-50mm. Waterproof and frost resistant.

## Coverage

4-5 m2 per 25kg bag @ 3.00mm thick  
1-2 m2 per 25kg bag @10.00mm thick

# SPECIAL SCREED



**Uzin NC194 Turbo (UZNC194)** - Turbo Light weight “bulk filling” screed system used for situations where structural strength cannot bear full screed systems. Can be used on timber & concrete substrates. Very good thermal and acoustic insulative properties. Full specialised systems. Seek technical advise. Interior use only.

## Coverage

2.6kg/m<sup>2</sup> per 20kg bag @ 10.0mm thick



**Uzin SC980 (NC198) Rapid Cement (UZSC98020)**  
For large cement screed areas without joints. Accelerated special cement for producing low shrinkage, dimensionally stable screeds, for interior and exterior use. Extremely low susceptibility to cracking. Ideal for bulk filling purposes.

Refer to Gilt Edge Industries Technical Data Sheet for consumption rates.



**Uzin SC966 (NC192) Rapid Screed (UZSC96620)**  
Pre mixed rapid screed mortar with very rapid drying. Mixes only with water, totally reliable in use, ideal for small areas, no waste material, very rapid setting and drying, saves time. Can be used interior and exterior. Ideal for bulk filling purposes.

## Coverage

1.5 m<sup>2</sup> per 30kg bag @ 10.0mm thick



# SUBSTRATE REPAIR



**Uzin KR 516 (UZKR516)** - Low odour casting and bonding resin for the quick restoration of cracks as well as bonding, fillings and repairs. Can be used in sensitive areas, no processing odour. No stirring tools required. Can be quickly worked on, short waiting time.

## Coverage

Approx. 100ml/running metre joint  
at 4 x 25mm  
2 x 300ml plastic bottles per unit



**Gilt Grip Repair Epoxy Kit 13kg (GGEPOXY13)** - is an epoxy system formulated to provide damage repair to concrete, wood and other common building materials. Structural adhesive—repair and refill of cracks in concrete and common building products. High impact strength areas—ramps, joint nosing's. Fills voids in damaged or spalled concrete. Grouting starter bars, load bearing bolts and base plates.

Kit includes: Resin, Hardener, Sand, Gloves & spread rate chart.

Refer to Gilt Edge Industries Ltd  
Technical Data Sheet within kit.

# MOISTURE CONTROL



## **Protect Crete Moisture Fix 15L (PCMFIX15L)**

Moisture Fix is a single pack one application, pour and spread, or low pressure spray system that deeply penetrates new or existing concrete, providing permanent water proofing, curing and protection.

## Coverage

4.5 m2 per Litre if sprayed



## **Protect Crete Densi Proof 20L (PCDENSI)**

Densi proof is a single pack one application spray on system that deeply penetrates new or existing concrete, provides permanent waterproofing curing and protection.

## Coverage

4.5 m2 per Litre

# MOISTURE CONTROL



**Uzin PE 480 Primer** (UZPE480) - 2 part epoxy moisture barrier for substrates with high residual moisture content. Trowel applied with B1 notched trowel and back rolled. Designed to be overlaid.

## Coverage

30 m<sup>2</sup> per 10kg Pail - (Single Coat)

**Note: Solid Timber Installations - 2 x coats required. 15 m<sup>2</sup> per 10kg Pail**



**Bostik Moisture Seal** (BOSMS) - is a 2 part water based epoxy coating designed as a moisture and vapour barrier membrane to prevent water seepage and permeation through concrete floors. The product shows excellent adhesion and acts as a surface preparation for subsequent adhesives when laying floor coverings of all kinds.

## Coverage

5 m<sup>2</sup> per Litre (Single Coat)

20 m<sup>2</sup> per 8 Litre Kit (Two Coats)

50 m<sup>2</sup> per 20 Litre Kit (Two Coats)

**Note: Finished system to be applied in two coats.**



**Selleys Liquid Nails VBS** (SLNVBS3.6) - A highly cross linked, pigmented, two pack epoxy vapour barrier system. For sealing concrete floor slabs to reduce the amount of water vapour emanating from the concrete. Suitable for use on concrete slabs prior to using Selleys Liquid Nails Direct Stick polyurethane timber flooring adhesive to lay timber flooring.

## Coverage

One full pack (3.6 Litre) is sufficient for 20m<sup>2</sup>. (6 m<sup>2</sup> per Litre)

**Note: Two coats maybe required in the case of very porous concrete.**



**Polymer 20 Hydrocoat** (R2020) - Hydrocoat 20 Moisture Barrier is a grey, two part water based epoxy sealer for concrete, masonry, fibrocement and other cementitious surfaces. Hydrocoat 20 may be mixed in equal parts by either weight or volume

## Coverage

4 m<sup>2</sup> per Litre (Single Coat)

40 m<sup>2</sup> per 20 Litre Kit (Two Coats)

**Note: Finished system to be applied in two coats.**

# WATERPROOFING



## Flexi Seal PUD Waterproof Membrane 15L (RFPWFLEX15)

Flexi Seal PUD is a blue, water based polyurethane modified , flexible water proofing membrane. Can be used over concrete, render, rendered brickwork, block work, fibre cement, plywood and particle board surfaces. Can be used for internal or external waterproofing applications.

**Coverage**  
1 m2 per 1.5L per two coats

# ACCESSORIES



**Silicate Sand 3-8mm 25kg** (UZ10606) - Fire dried quartz with gram size 0.3—0.8mm as a filler and four surface gritting. For filing and thickening pouring and bonding resins to give a homeogenous mortar. Produces a gritted surface. Fills and adjusts consistency. For interior and exterior use.



**Uzin Levelling Pins** (UZ61834) - Plastic self adhesive height measurement pins for use when pouring levelling compounds.



**Uzin Reinforcement Fibre 250gm**  
(UZ11725) - Alkaline resistant glass fibre for increasing the structural strength of self levelling smoothing compounds.



# ACCESSORIES



**5L Measuring Jug** (RFPMJ) - Easy measurement of water quantity for powder products.



**Uzin Water Bucket 9L** (UZ10412) - Transparent plastic bucket with printed litre scale. Ideal for measuring the correct water quantity for powder products.



**Uzin Blue Mixing Bucket 30L** (UZ9191)—Great size and strength. Easy handling for mixing of levelling compounds.

# ACCESSORIES



**Wolff Professional Levelling Compound Rake** (W52298) - For applying self levelling compounds.

R2 Blade (W13396) - 2.0mm Approx spread rate.

R3 Blade (W51546) - 3.0mm Approx spread rate.



**Wolff Professional Spike Roller** - For venting compounds and coatings. Splash guard included. Telescopic handle connector.

25cm (W14272) with 21mm pin length

50cm (W13636) with 31mm pin length



**Wolff Professional Spike Shoes** (W51549). For walking on coated or filled substrates and surfaces. Included is 1 x spare set of nails and 2 x spare straps. Once size fits all.



**Wolff Specialised Stirrer KR Type** (W13606) - Very high shear forces, easy to clean, suitable for viscous adhesive or seals and gypsiferous or bituminous materials. Ideal for mixing levelling compounds. Prevents clotting.



**Wolff Professional Smoothing Trowel** (W56203)

280mm x 135mm Blade.

Solid Construction and ergonomic control handle.



**Wolff Professional Levelling Compound Trowel** (W56204)

500mm x 135mm Blade.

Solid construction with ergonomic control handle.

# ACCESSORIES



**1600W Electric Hand Mixer (TM678281)** - This mixer is a heavy duty floor preparation mixer. It is used for mixing flooring compounds quickly and thoroughly.

Double Handle

140mm Paddle

40-90L Volume Capacity



**Porta Mix (Hippo) & Mix Paddle (PPPM)** - Mixes, delivers and spreads material quickly with excellent control. Handles wide range of construction compounds. Easy operation by one person. Reduces time, effort and labour costs. Thorough mixing, blending and replacement without mess. Dust extraction port for dust control. Easy to clean out. Bowl capacity 6 x 20kg mix plus water (85L/160kg)



[www.giltedge.co.nz](http://www.giltedge.co.nz)

EMAIL: [help@giltedge.co.nz](mailto:help@giltedge.co.nz)

FREE PHONE: 0800 445 833

FREE FAX: 0800 103 649